



专业研发 / 制造 / 销售

# 特种液晶显示屏制造商

MANUFACTURER  
OF SPECIAL LCD DISPLAYS

## 产品目录

2023.6

深圳市如新电子有限公司

# Contents

目录 ▶

## 全系列液晶产品

---

- 1 高亮液晶屏系列
- 2 条形液晶屏系列
- 3 透明液晶屏系列
- 4 中小尺寸液晶屏系列
- 5 异形液晶屏系列
- 6 液晶屏整机系列
- 7 会议一体机系列

# 高亮液晶屏系列

亮度可订制：500-5000 cd/m<sup>2</sup>      背光结构：侧入式，直下式

序号	尺寸	型号	亮度	功耗	分辨率	显示区域	外形尺寸	接口定义
1	15.0	LCMA-RX0150GB03-C100	1000	16.6	1024*768	304.128*228.096	326.5*253.5*9.7	LVDS (1 ch, 8-bit)
2	15.6	LCMA-RX0156GI01-C100	1000	14	1920*1080	344.16*193.59	360*212.3*6.3	eDP (2 Lanes)
3	18.5	LCMA-RX0185GB06-C100	1000	28	1920*1080	408.96*230.04	430.37*254.6*11.2	LVDS (2 ch, 8-bit)
4	21.5	LCMA-RX0215GB08-C150	1500	54	1920*1080	476.64*268.11	502.8*299.18*16	LVDS (2 ch, 8-bit)
5	21.5	LCMA-RX0215GB16-C100	1000	40	1920*1080	476.64*268.11	495.6*292.2*9.5	LVDS (2 ch, 8-bit)
6	27.0	LCMA-RX0270GA07-C100	1000	62	1920*1080	597.6*336.15	630*368.2*13	LVDS (2 ch, 8-bit)
7	32.0	LCMA-RX0320GB01-C150	1500	76.5	1920*1080	698.4*392.85	729.4*424.2*29.5	LVDS (2 ch, 8-bit)
8	32.0	LCMA-RX0320GL20-Z200	2000	97	1920*1080	698.4*392.85	731.9*431.4*56	LVDS (2 ch, 8-bit)
9	32.0	LCMA-RX0320GL18-C120	1200	59	1920*1080	698.4*392.85	729.4*424.2*29.5	LVDS (2 ch, 8-bit)
10	43.0	LCMA-RX0430GB02-C150	1500	101	1920*1080	941.18*529.42	973.2*561.5*29.5	LVDS (2 ch, 8-bit)
11	43.0	LCMA-RX0430GB07-Z250	2500	136	1920*1080	940.9*529.25	973.8*567*56.4	LVDS (2 ch, 8-bit)
12	49.0	LCMA-RX0490GL10-C150	1500	158	3840*2160	1073.78*604	1103.8*634*31.5	V-by-One 8 lane
13	49.0	LCMA-RX0490GL14-Z350	3500	288	3840*2160	1073.78*604	1106.4*641.6*57.5	V-by-One 8 lane
14	55.0	LCMA-RX0550GB07-Z200	2000	240	1920*1080	1209*680.4	1233.6*704.4*55	LVDS (2 ch, 10-bit)
15	55.0	LCMA-RX0550GL24-Z200	2000	311	1920*1080	1209.6*680.4	1242.1*718*58.1	V-by-One 8 lane
16	65.0	LCMA-RX0650GL05-Z200	2000	330	3840*2160	1428.5*803.5	1461*843.1*59.5	V-by-One 8 lane
17	65.0	LCMA-RX0650GB06-Z250	2500	545	3840*2160	1428.48*803.52	1452.4*827.5*64.8	V-by-One 8 lane
18	75.0	LCMA-RX0750GB02-Z350	3500	760	3840*2160	1649.7*927.9	1683*975.4*55.3	V-by-One 8 lane

# 条形液晶屏系列

 亮度可订制：500-3500 cd/m<sup>2</sup>    尺寸可订制切割

序号	尺寸	型号	亮度	功耗	分辨率	显示区域	外形尺寸	接口定义
1	13.8	LCMA-RX0138TQ01-C070	700	4.5	1920*358	344.16*61.17	371.5*90.1*12.7	LVDS (2 ch, 8-bit)
2	14.9	LCMA-RX0149TB03-C070	700	7	1028*204	374.78*60	399.78*81*12.88	LVDS (2 ch, 8-bit)
3	15.3	LCMA-RX0153TB02-C070	700	8.5	1280*342	374.78*100.14	396*124*13	LVDS (2 ch, 8-bit)
4	16.4	LCMA-RX0164TB01-C070	700	9	1366*230	409.7*69	431.8*94.8*14.7	LVDS (1 ch, 8-bit)
5	16.8	LCMA-RX0168TB01-C070	700	8	1366*384	409.7*115.2	431.8*141*14.7	LVDS (1 ch, 8-bit)
6	17.2	LCMA-RX0172TB02-C050	500	9	1920*714	408.96*152.1	439*179.3*19.15	LVDS (2 ch, 8-bit)
7	19.2	LCMA-RX0192TA02-C050	500	12	1920*360	476.64*89.37	496*109.2*11.88	LVDS (2 ch, 8-bit)
8	19.4	LCMA-RX0194TA03-C100	1000	20	1920*510	476.64*126.6	495.6*150.7*12	LVDS (2 ch, 8-bit)
9	19.7	LCMA-RX0197TB01-C100	1000	23.5	1920*624	476.64*154.9	497.4*179.4*14.5	LVDS (2 ch, 8-bit)
10	21.9	LCMA-RX0219TA01-C100	1000	25	1920*712	527.04*195.5	548.4*222.2*14.5	LVDS (2 ch, 8-bit)
11	27.5	LCMA-RX0275TA01-C070	700	10	1920*136	698.4*50	714.4*75*19.2	LVDS (2 ch, 8-bit)
12	28	LCMA-RX0280TA03-C100	1000	21	1920*360	698.4*130.9	732*165*17.3	LVDS (2 ch, 8-bit)
13	28.6	LCMA-RX0286TA01-C050	500	TBD	1920*540	698.4*196.43	732*231.6*19.4	LVDS (2 ch, 8-bit)
14	35.6	LCMA-RX0356TL02-C050	500	42	1900*2160	598.5*680.4	628.6*711*18.7	V-by-One 8 lane
15	35.6	LCMA-RX0356TA01-C050	500	31	1900*2160	598.5*680.4	628.6*711*18.5	V-by-One 8 lane
16	36.6	LCMA-RX0366TA02-C100	1000	32	1920*290	919.296*138.85	960*174.35*16.9	LVDS (2 ch, 8-bit)
17	37.6	LCMA-RX0376TI01-Z200	2000	79	1920*540	919.3*258.55	947.3*293.55*55	LVDS (2 ch, 8-bit)
18	38	LCMA-RX0380TB01-C070	700	38.2	1920*540	919.3*258	955.9*304.6*19	LVDS (2 ch, 8-bit)
19	49.5	LCMA-RX0495TL01-C025	250	33.5	3840*1080	1209.6*340.2	1241.45*364.7*26	V-by-One 8 lane
20	49.5	LCMA-RX0495TL02-C100	1000	92	1920*540	1209.6*340.2	1240.2*370.8*24.5	V-by-One 8 lane

# 透明液晶屏系列

操作系统可选 尺寸可订制

序号	尺寸	亮度	分辨率	外形尺寸	显示区域	对比度	功耗	系统
1	21.5"	500	1920*1080	533*410*350	475*298	4000:1	60	安卓/Windows
2	32"	500	1920*1080	826*521*400	706*401	4000:1	80	安卓/Windows
3	43"	500	1920*1080	1069*657*400	949*537	4000:1	100	安卓/Windows
4	49"	500	1920*1080	1202*732*400	1082*612	4000:1	220	安卓/Windows
5	55"	500	1920*1080	1338*809*400	1218*689	4000:1	280	安卓/Windows
6	65"	500	1920*1080	1577*952*400	1437*812	4000:1	280	安卓/Windows
7	75"	500	1920*1080	1819*1097*400	1659*937	4000:1	300	安卓/Windows
8	86"	500	1920*1080	2064*1235*400	1904*1075	4000:1	380	安卓/Windows
9	90"	500	1920*1080	2250*1350*500	1992.96*1121.04	4000:1	380	安卓/Windows

# 中小尺寸液晶屏系列

## FOG投影屏系列

编号	品名	型号	接口	FPC/PIN	FPC长度	分辨率	色域	透过率
1	2寸	FOG-RX020T-0800-V1	LVDS	30PIN	42.62mm	TN/240*320	40%	4.50%
2	2.4寸	FOG-RX024B-0300-V0	LVDS	30PIN	67.1mm	IPS/800*480	45%	6.30%
3	2.6寸	FOG-RX026J-0100	LVDS	30PIN	70mm	IPS/1280*720	45%	6.00%
4	2.6寸	YT-B026-0400	LVDS	30PIN	53.96mm	IPS/640*360	45%	4.30%
5	3.8寸	FOG-RX038T-0400	LVDS	30PIN	59mm	IPS/1024*600	45%	5.50%
6	4寸	FOG-RX040I-0100	LVDS	30PIN	60mm	IPS/1280*720	60.8%	6.2%
7	4寸	FOG-RX040B-3500	LVDS	60PIN	60mm	IPS/1920*1080	50%	6.00%
8	4.41寸	FOG-RX045B-1800	LVDS	30PIN	60mm	IPS/1920*1080	45%	6.05%
9	4.45寸	FOG-RX045B-0200	LVDS	60PIN	60mm	IPS/1920*1080	50%	6.00%
10	5寸	FOG-RX050I-0100	LVDS	60PIN	63mm	IPS/1920*1080	55%	6.20%
11	5.7寸	RX058B-0600	LVDS	60PIN	60mm	IPS/1920*1080	60%	6.00%
12	5.7寸	FOG-RX058B-1800	LVDS	60PIN	65mm	IPS/1920*1080	55%	5.80%
13	5.7寸	FOG-RX058B-2600	LVDS	60PIN	65mm	IPS/1920*1080	55%	6.20%
14	5.7寸	FOG-RX058B-2800	LVDS	60PIN	65mm	IPS/1920*1080	45%	6.20%
15	6.7寸	RX067B-0100	LVDS	40PIN	65mm	IPS/1920*1080	40%	5.70%

# 中小尺寸液晶屏系列

## 模组产品系列

序号	尺寸	型号	规格	分辨率	亮度	接口	外形	接口方式
1	1.44	RX014C-0100	LCM	TN/128*128	250	SPI+MCU	方屏	22PIN/插接
2	1.77	RX018CN3502772	LCM	TN/128*160	250	SPI+MCU	竖屏	20PIN/插接
3	2.0	RX020F-1100	LCM	TN/176*220	250	SPI+MCU	竖屏	20PIN/插接
4	2.4	RX024H-2900-CTP	LCM+CTP	IPS/240*320	500	SPI+RGB	竖屏	10PIN/插接
5	2.8	RX028F-2200-CTP	LCM+CTP	TN/240*320	250	SPI+MCU	竖屏	40PIN/插接
6	2.8	RX028F-2300-RTP	LCM+RTP	TN/240*320	250	SPI+MCU	竖屏	33PIN/插接
7	3.5	RX035H-19-RTP	LCM+RTP	TN/320*480	250	SPI+MCU	竖屏	40PIN/插接
8	3.5	RX035B-0200-CTP	LCM+CTP	IPS/480*800	250	MINPIN	竖屏	25PIN/插接
9	4.0	RX040B-1702-CTP	LCM+CTP	IPS/480*800	650	MINPIN	竖屏	39PIN/插接
10	4.3	RX043C-0201-CTP	LCM+CTP	TN/480*272	300	RGB	横屏	40PIN/插接
11	4.3	RX043C-8002-RTP	LCM+RTP	TN/480*272	600	RGB	横屏	45PIN/插接
12	4.3	RX043I-4706	LCM	TN/480*272	500	RGB	横屏	40PIN/插接
13	5.0	RX050A-1400	LCM	TN/800*480	500	RGB	横屏	40PIN/插接
14	5.0	RX050I-2700	LCM	TN/800*480	600	RGB	横屏	40PIN/插接
15	5.7	RX058B-0600	LCM	IPS/1920*1080	1000	LVDS	横屏	60PIN/插接
16	5.8	RX058B-0100	LCM	TN/1280*768	1000	LVDS	横屏	60PIN/插接
17	7.0	RX070B-0301-CTP	LCM+CTP	IPS/1024*600	500	LVDS	横屏	40PIN/插接
18	7.0	RX-A07C3550-FW	LCM	TN/800*480	300	RGB	横屏	50PIN/插接
19	10.1	RX101I-0200-CTP	LCM+CTP	IPS/1280*800	500	LVDS	横屏	40PIN/插接



# 异形液晶屏系列

## 方屏产品系列

序号	尺寸	型号	亮度	功耗	分辨率	显示区域	外形尺寸	对比度
1	21.6	LCMA-RX0216TL02-C040	400		1798*1338	441*328	465*351.97*14	1000:1
2	22	RX220FXP01-V01	400	36	1920*1920	394.56*394.56	412.56*412.56*21.8	1000:1
3	33.2	RX332FXP01-V01	500	60	1920*1920	596.16*596.16	615.96*615.96*21.8	1000:1
4	35.6	LCMA-RX0356TA01-C050	500		1900*2160	598.5*680.4	628.6*711*18.5	1300:1
5	42.1	RX421FXP01-V01	500		1900*2160	706.8*803.5	737.9*835	1300:1
6	48.7	RX487FXP01-V01	500		1900*2160	816.2*927.9	847*960	1300:1
7	52.2	RX522FXP01-V01	500		1900*1900	937.65*937.65	978*978	1300:1
8	56.15	RX561FXP01-V01	500		1900*2160	947.5*1065.9	977.5*1095.9	1300:1
9	52.75	RX527FXP01-V01	500		1900*2160	947.5*947.5	977.5*1126	1300:1
10	55.9	RX559FXP01-V01	500		1900*2160	937.65*1065.94	978*1105	1300:1

## 圆屏产品系列

序号	尺寸	型号	亮度	功耗	分辨率	显示区域	外形尺寸	对比度
1	23.6	RX-0236YA-C070	700	55	848*848	600.384*600.384	663*663*45.7	4000:1



## 液晶屏整机系列

序号	尺寸	切割后型号	亮度	功耗	分辨率	显示区域	外形尺寸	接口定义
1	15寸	LCMA-RX0150ZJ01-C025	250	4	1024*768	304.128*228.096	329.1*285.5*17.6	LVDS (1 ch, 8-bit)
2	15.6寸	LCMA-RX0156ZJ01-Z400	4000	TBD	1920*1080	344.78*193.59	369.78*222.29*64.9	/
3	19.2寸	LCMA-RX0192ZJ01-C050	500	8	1920*360	476.64*89.37	499*112.6*32	LVDS (2 ch, 8-bit)
4	19.4寸	LCMA-RX0194ZJ01-C070	700	15	1920*510	476.68*126.6	500*150*32	LVDS (2 ch, 8-bit)
5	21.5寸	LCMA-RX0215ZJ08-Z500	5000	127	1920*1080	476.64*268.11	509.33*297.75*65	LVDS (2 ch, 8-bit)
6	21.5寸	LCMA-RX0215ZJ05-C050	500	19.2	1920*1080	476.064*267.786	489.4*279.84*29.4	LVDS (2 ch, 8-bit)
7	27.5	LCMA-RX0275ZJ01-C100	1000	12	1920*137	698.4*50	722.1*78.8*25	LVDS (2 ch, 8-bit)
8	29.6寸	LCMA-RX0296ZJ02-C200	2000	75	1920*760	698.4*276.5	735.5*309.95*45	LVDS (2 ch, 8-bit)
9	32寸	LCMA-RX0320ZJ02-C003	30	TBD	1920*1080	696.96*392.04	777*475*58	eDP (2 Lanes)
10	36.2寸	LCMA-RX0362ZJ02-C150	1500	68	1920*540	885.6*280.8	915.6*279.8*45.7	LVDS (2 ch, 10-bit)
11	38寸	LCMA-RX0380ZJ01-C070	700	TBD	1920*539	919.3*258	987.06*307.17*78	LVDS (2 ch, 8-bit)
12	38.5寸	LCMA-RX0385ZJ01-C045	450	32	1920*540	940.896*264.63	967.9*296.26*24.9	LVDS (2 ch, 8-bit)
13	43寸	LCMA-RX0430ZJ01-C100	1000	98.5	1920*1080	941.18*529.42	983.2*571.5*50	LVDS (2 ch, 8-bit)
14	48寸	LCMA-RX0480ZJ01-Z400	4000	150	3840*540	1209.6*170.1	1239*208*90	V-by-One 8 lane
15	49.5寸	LCMA-RX0495ZJ01-C070	700		1920*540			LVDS (2 ch, 10-bit)
16	49.5寸	LCMA-RX0495ZJ03-C100	1000	85	1920*540	1209.6*340.2	1239.6*370.2*45	LVDS (2 ch, 10-bit)
17	65寸	LCMA-RX0650ZJ03-Z200	2000	350	1920*1080	1428.5*803.5	1466*848.1*127	V-by-One 8 lane

# 会议一体机系列

亮度可订制：500-3500 cd/m<sup>2</sup>    尺寸可订制切割

序号	尺寸	型号	亮度	功耗	分辨率	显示区域	外形尺寸	系统
1	55寸	RX55DB	300	120	3840*2160	1210*681	1277.6*772*88.8	安卓
2	65寸	RX65DB	280	120	3840*2160	1429.3*804.9	1496.7*895.2*88.8	安卓
3	70寸	RX70DB	300	150	3840*2160	1539*867	1607.7*975.2*103.4	安卓
4	75寸	RX75DB	320	380	3840*2160	1652*930	1722*1038.2*92.8	安卓
5	85寸	RX85DB	350	350	3840*2160	1871.4*1053.6	1964*1174.4*94.5	安卓
6	86寸	RX86DB	350	350	3840*2160	1895*1065	1964*1174.4*105.7	安卓
7	98寸	RX98DB	450	480	3840*2160	2160*1215	2221.7*1318.9*105.5	安卓

# 诚信共赢

持续为客户创造长期价值



## 总部

📍 深圳市宝安区西乡街道桃源社区园艺园26栋B5层

☎ 86-0755-29850482

🌐 [www.rogin.com.cn](http://www.rogin.com.cn)

## 深圳生产基地

📍 深圳市宝安区沙井街道共和第八工业区

## 湖北生产基地

📍 湖北省襄阳市宜城市经济开发区